



# SHANGHAI E-TANG TRADING CO.,LTD

Room 401, No.57, Lane 2999, Caobao Road, Minhang District, Shanghai, China  
Tel: 0086-13381591129/15921292120 Fax: 0086-21-34520355 Zip code: 201101

## Material Safety Data Sheet

### Section I - Identification of the product and of the company

Ceramic fiber bulk CRF-00

SHANGHAI E-TANG TRADING CO., LTD.

ROOM 401, BUILDING #57, NO.2999, CAOBAO ROAD, SHANGHAI, CHINA

Tel: 0086-21-34520355/0086-15921292120 Fax: 0086-21-34520355

### Section II - Composition/Information on Ingredients

It is produced by spun yarn made of high quality aluminum silicate refractory fiber produced by blowing technology.

Ingredient Name	CAS Number	Percent
Aluminum silicate fiber		>98%
Impurity		<2%

### Section III - Hazardous Identification

Warning dust from this product generated by handling may cause skin, eye and respiratory tract irritation. Possible hazards depend on duration and level of exposure.

Hazard ratings

Hazardous Materials information system(HMIS) Ratings:

Health: 1 Flammanility:0 Ractivity:0 Personal Protection Index: X

Possible effects on health: prolonged and repeated inhalation of aluminum silicate dust may cause chronic effects on respiratory system such as bronchitis, asthma, and emphysema signs

And symptoms of excessive exposure:

Eye contact: physical irritation

Skin contact: physical irritation

Ingestion: temporary irritation to gastrointestinal tract

Inhalation: pulmonary dysfunction

### Section IV - First Aid Measures

EYE CONTACT:



# SHANGHAI E-TANG TRADING CO.,LTD.

Room 401, No.57, Lane 2999, Caobao Road, Minhang District, Shanghai, China  
Tel: 0086-13381591129/15921292120 Fax: 0086-21-34520355 Zip code: 201101

---

If eyes become irritated, wash immediately with large amounts of lukewarm water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Do not rub eyes. Get medical attention if irritation persists.

#### SKIN CONTACT:

If skin becomes irritated, do not rub or scratch exposed skin. Wash area of contact thoroughly with soap and water. Using a skin cream or lotion after washing may be helpful. Change into clean clothing.

INGESTION: relocate affected individual to an environment of clean and fresh air. Drink plenty of water seek medical help if symptoms persist.

INHALATION: remove affected individual to a dust free place, seek medical help if irritation persists.

Notes to physicians: Skin and respiratory effects are the result of mechanical irritation: fiber exposure does not result in allergic manifestations.

---

#### Section V-Fire Aid Measures

---

Non-combustible (does not burn) product.

Auto-ignition temperature: none

NFPA Unusual Hazards: none

Unusual fire and explosion hazards: none

Extinguishing Media: use proper extinguishing media for the surrounding fire.

Firefighting protective equipment: wear full bunker gear including positive pressure self-contained breathing apparatus.

---

#### Section VI-Accidental Release Measures

---

Avoid creating airborne dust. Maintain routine housecleaning procedures. Vacuum only with HEPA filtered equipment, if sweeping is necessary, use a dust suppressant and keep material in closed containers. Do not use compressed air for clean-up. Workers should wear gloves, goggles and approved respirator. Avoid clean-up procedures that could cause water pollution.

---

#### Section VII-Handling, Storage and Disposal

---

##### CLEAN-UP

Clean up dust carefully. Use wet sweeping or high efficiency vacuum to remove dust. Do not use compressed air.

During after-service removal activities, wet exposed material frequently to minimize airborne dust. A surfactant may be added to the water to improve the wetting process. Use only enough water to wet the insulation. Do not allow water to accumulate on floors.

---



# SHANGHAI E-TANG TRADING CO.,LTD

Room 401, No.57, Lane 2999, Caobao Road, Minhang District, Shanghai, China  
Tel: 0086-13381591129/15921292120 Fax: 0086-21-34520355 Zip code: 201101

---

## EMPTY CONTAINERS:

Product packaging may contain residue. Do not reuse.

---

## Section VIII- Exposure controls/personal protection

---

Components OSHA supplier

Aluminum silicate fiber None established

ACGIH TLV: Aluminum silicate fiber—none established

For Aluminum silicate fiber, refer to OSHA guidance regarding "Particulates not otherwise Regulated" (PNOR). Control airborne dust levels as follows:

Components Particle size OSHA

PNOR total dust 15mg/m<sup>3</sup>

Respirable dust 5mg/m<sup>3</sup>

ACGIH particulates not otherwise classified (PNOC)—INHALABLE PARTICULATE: 10mg/m<sup>3</sup>. RESPIRABLE PARTICULATE: 3mg/m<sup>3</sup>

Other Occupational Exposure Levels (OEL)

RCF-related occupational exposure limits vary from country to country. Listed here are a few regulatory OEL examples:

Australia--0.5f/cc; Austria—0.5f/cc; Canada—0.5 to 1 f/cc; Denmark—1 f/cc

France—0.6 f/cc; Germany—0.5 f/cc; Netherlands—1 f/cc; United Kingdom—2 f/cc

Example is: RCFC REG 0.5 f/cc. The objectives and criteria underlying each of these OEL decisions also vary. The evaluation of occupational exposure limits and determining their relative applicability to the workplace is performed on a case-by-case, by a qualified industrial hygienist.

Engineering Controls:

Use engineering controls such as ventilation and dust collection devices to limit airborne fiber concentrations to the minimum attainable level.

Eye Protection:

In case of overhead work, wear goggles or safety glasses with side shields to prevent eye contact.

Skin Protection:

Wear gloves, head covering and full body clothing as necessary to prevent skin irritation.

Respiratory Protection:



# SHANGHAI E-TANG TRADING CO.,LTD.

Room 401, No.57, Lane 2999, Caobao Road, Minhang District, Shanghai, China  
Tel: 0086-13381591129/15921292120 Fax: 0086-21-34520355 Zip code: 201101

When effective engineering and administrative controls are insufficient, the use of appropriate respiratory protection, pursuant to the requirements of OSHA 1910.134 and 29 DFR 1926.103 for the particular hazard or airborne concentrations in the work place, it is recommended. For dust concentrations below applicable exposure limit value.

## Section IX-Physical and Chemical Properties

Ceramic Fiber

Oxidizing properties: None

Vapor density: not applicable

Odor: None

Water solubility: not applicable

Chemical family: Aluminum silicate fibers

PH: not applicable

Boiling Point: not applicable

Melting point: 1760C

Chemical Indexes

Al <sub>2</sub> O <sub>3</sub>	Al <sub>2</sub> O <sub>3</sub> +SiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub> +SiO <sub>2</sub> +ZrO <sub>2</sub>	ZrO <sub>2</sub>	Fe <sub>2</sub> O <sub>3</sub>	Na <sub>2</sub> O-K <sub>2</sub> O
46	97	-	-	<1.0	≤0.5

Glass Fiber reinforcement

Melting Point(Softening): 800°C

Boiling Point (°C): Not applicable

Specific Gravity (Bare Glass): 2.59

Percent Volatile: N/A

Vapor Pressure (mm/Hg): not applicable

Vapor Density (Air=1): Not applicable

Evaporative Rate (Ethy1 Ether=1): not applicable

Solubility in water: Not Soluble

Appearance and Odor: White/Off-white/tan colored solid with no odor

PH not applicable

Chemical Indexes

SiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	CaO	MgO	R <sub>2</sub> O	Fe <sub>2</sub> O <sub>3</sub>
67%+/-0.5	6.2%+/-0.4	9.5%+/-0.3	4.2%+/-0.3	12%+/-4	<0.4%
C	Si	S	Mn	Ni	Cr
0.08%	1%	0.05%	2%	8%	17%

## Section X-Stability and Reactivity

Chemical stability: stable under conditions of normal use.

Incompatibility: hydrofluoric acid, and concentrated alkali.

## Section XI-Toxicological information

Chemical stability: stable under conditions of normal use.

Epidemiological studies conducted by institution of human environment protection in China has provided no evidence that there is a direct cause-and effect relationship between cumulative exposure to aluminum silicate fibers and lung cancers or particular





# SHANGHAI E-TANG TRADING CO.,LTD

Room 401, No.57, Lane 2999, Caobao Road, Minhang District, Shanghai, China  
Tel: 0086-13381591129/15921292120 Fax: 0086-21-34520355 Zip code: 201101

---

pulmonary diseases.

However recent toxicological experiments using physiological exposure method(inhalation)have produced findings of respiratory disease in rodents, Aluminum silicate refractory fiber has found to be a rodent carcinogen under the conditions that the rodents are exposed to high levels of the material(75—115fibers/cc)on a basis of lifetime duration.

---

## Section XII-Ecological information

---

No data is available on adverse effects of the material on the environment.

---

## Section XIII-Disposal considerations

---

As produced, this material is usually accepted for disposal at most sites licensed for the disposal of industrial waste. Check applicable regulations and waste site policies prior to disposal. Waste should be placed in sealed containers for disposal.

In case of contamination, by other materials classified as hazardous waste, expert guidance should be sought.

---

## Section XIV-Transport information

---

Product should remain in sealed containers during transportation.

---

## Section XV-Regulatory information

---

CERCLA: the aluminum silicate fibers of this product have an average diameter of 2-4 um and are not considered CERCLA hazardous substances (CERCLA 40 CFR302)

Clean Air Act (CAA): thermal insulation fibers are composed of (RCF) with an average diameter greater than 1 micron, and therefore are not considered hazardous air pollutants.

Toxic Substances Control Act (TSCA): all substances in this product are listed, as required, on the TSCA chemical inventory.

### State Regulations

California: aluminum silicate fiber has not been listed by the State of California on proposition 65, the Safe Drinking Water and Toxic Enforcement Act of 1986.

New Jersey: Chemicals which are listed as special health hazard substances as defined in New Jersey worker and Community Right to know Act, New Jersey Administrative code, title 8, Department of health, Chapter 59, Subchapter 10

Pennsylvania: aluminum silicate fiber is not listed as a special health hazard substance as defined in Pennsylvania

---



# SHANGHAI E-TANG TRADING CO.,LTD.

Room 401, No.57, Lane 2999, Caobao Road, Minhang District, Shanghai, China  
Tel: 0086-13381591129/15921292120 Fax: 0086-21-34520355 Zip code: 201101

Right-to-Know Law, Section 3800.

Chemical Name CAS Number

None 142844-00-6

International Regulations:

Canadian Workplace Hazardous Materials Information System (WHMIS):

No Canadian Workplace Hazardous Materials Information System categories apply to this product.

Canadian Environmental Protection Act (CEPA):

All substances in this product are listed, as required, on the Domestic Substances List (DSL). Chemicals which are listed on the Non-Domestic Substances list:

Chemical Name CAS Number

None

---

## Section XVI-Other information

---

Removal after service: Under sustained and steady high temperature over 1800°F, this material will possibly transform to crystalline silica (cristobalite) in exposed portions. Prolonged or repeated exposure to respirable crystalline silica dust may lead to lung diseases. IARC has listed crystalline silica in Category 2A a probable carcinogen ("crystalline silica inhaled in the form of quartz or cristobalite from occupational source is carcinogenic to humans" IARC monograph 68, June 1997 p 210—211). The permissible exposure limit (PEL) set by OSHA for respirable cristobalite is 0.05mg/m<sup>3</sup>. Whenever possible follow section 8 procedures for exposure controls and personal protection.

Abbreviations:

CERCLA: comprehensive environmental response compensation and liability act of 1980

CAS; Chemical abstracts service

F/CC: fibers per cubic centimeter

HMIS: Hazardous Material information system

Mg/m<sup>3</sup>: Milligrams per cubic meter of air

NIOSH: National institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PEL: permissible exposure limit





# SHANGHAI E-TANG TRADING CO.,LTD.

Room 401, No.57, Lane 2999, Caobao Road, Minhang District, Shanghai, China  
Tel: 0086-13381591129/15921292120 Fax: 0086-21-34520355 Zip code: 201101

---

SARA: super amendments and reauthorization act

TSCA: toxic Substances Controls Act

To the best of our knowledge, the information contained herein is accurate. The information provided is based upon data furnish by E-TANG. Assume liability whatsoever for the accuracy or completeness of the information contained herein. While believed to be reliable, the information of products is intended for use by skilled persons at their own risk. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that those are the only hazards that exist.

