



# SHANGHAI E-TANG TRADING CO.,LTD.

ROOM 401, BUILDING #57, NO.2999, CAOBao ROAD, SHANGHAI, CHINA

Tel: 0086-21-34520355/0086-15921292120 Fax: 0086-21-34520355

## Technical Data Sheet

### EGT61-BK



#### Description:

It is EGT61 impregnated with graphite which increases resistance to abrasion and flame, high temperature absorb mote.

#### Application:

Provide protection of industrial wires, cables, hoses, tube and pipe and also provide thermal insulation and personnel protection. Also used as a gasket or seal.

#### Physical Properties:

Thickness (mm)	Width (mm)	Density (g/m <sup>2</sup> )	Weaving structure	Yarn thickness (tex)		Yarn count(pc/cm)		Roll length (m)
				Warp	Weft	Warp	Weft	
1.5	10-200	1100	Plain	1000	480	7.2	3.9	30 or 50
2	10-200	1400	Plain	1720	480	5.8	3.0	
2.5	13-200	1750	Plain	2000	480	5.8	3.0	
3	13-200	2000	Plain	2700	1200	4.8	1.9	
6	20-200	3800	Twill	3600	1500	7.0	1.7	

#### Remarks

1. The data above are typical values only, and should not be used for specifications purpose.
2. The products should be stored at room temperature, kept away from wet and heat source.
3. The users should take test and do trial-application on the above products before coming into application so as to witness and ensure suitability for their special purpose and technique.

